

**SCHEMA TECNICA N°76**

ESTERN STUCCO

Powder filler for internal and external use

DESCRIPTION

ESTERN STUCCO is a powder filler for internal and external use, designed for plastering and restoring surfaces such as walls, frames, rosettes, drywall, etc..

The product is recommended for leveling small cracks or slight depressions.

ESTERN STUCCO can also be sanded after application.

APPLICATION

New Walls:

-The surface to be treated must be dry. Conditions and thickness of the plaster layer affect the drying and hardening time, so make sure it has at least 28 days of curing time.

- Brush the surface, in order to remove any loose leaf flakes and ensure that any rust traces is cleaned up.

- Proceed applying ESTERN STUCCO, with a stainless steel spalter, ready to use or diluted with water as necessary.

Old Walls:

-The surface to be treated must be dry.

-Scrape off any loose flaking and poorly adhering coating, scraping and washing the surface with plenty of water or using a pressure washer.

-Proceed following the instruction of 'NEW WALL' from the third point onwards.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273


P.IVA 01122590753

www.rivedil.com - export@rivedil.com

TECHNICAL DATA

Nature of the bond	Special fillers
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Water secondo necessità
Yield	secondo supportom ² /Kg
Specific weight	N/A
Colors	white
Dry aspect	
Wet aspect	white powder paste
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	5KG,1KG

CHARACTERISTICS

Characteristics:	Linea stucchi.
Can be applied on:	Walls,Wood.
for:	Interno ed Esterno.
Certifications:	

TOOLS AND RELATED PRODUCTS

Tools:	Spalter inox.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR76** safety data sheet.

ITEM SPECIFICATION

Powder filler for external and internal use. Applications to be made on already prepared surfaces of ESTERN STUCCO, based on special fillers, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.

**COLORIFICIO RIVEDIL di COSIMO CODARDO**

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

PIVA 01122590753

www.rivedil.com - export@rivedil.com