

PREVENIL DM200

DESCRIPTION

PREVENIL DM200 is an anti-mold, used as additive for water based paints.

It restores walls from the most difficult agent such as mold, which is often present in cold and warm environments.

It shall be sufficient to mix PREVENIL DM200 into paint by using a paddle mixer and in order to achieve a better result, simply increase the percentage of PREVENIL DM200.

APPLICATION

By using a paint mixer, mix PREVENIL DM200 with paint, following these proportions:

- 1 x 0.500 pack of PREVENIL DM200 for 14 liter paint bucket
- 1 x 0.250 pack of PREVENIL DM200 for 4 liter paint bucket

It is recommendable to follow the instructions in the APPLICATION section of the additive painting technical sheet.

TECHNICAL DATA	
Nature of the bond	N/A
Viscosity	
Drying Time	h complete.
Thinning	Ready to use
Yield	m ² /Lt
Specific weight	N/A
Colors	
Dry aspect	
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	0,500LT,0,250LT
CHARACTERISICS	
Characteristics:	Linea Isolanti.
Can be applied on:	Walls,Wood.
for:	Interno ed Esterno.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	.
Related products:	.

SAFETY INSTRUCTIONS

The product does not require labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates.

Use the product in accordance with the relevant health and safety regulations of the country.

Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste.

For further information please refer to **SSR120** safety data sheet.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO

Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy

Tel. (+39) 0832 731293 - (+39) 0832 731273

P.IVA 01122590753

www.rivedil.com - export@rivedil.com