

IMPERMEABILIZZANTE PER TERRAZZE

Water- repellent paint with added bituminous quartz powder, suitable for solar floors.

DESCRIPTION


IMPERMEABILIZZANTE PER TERRAZZE is a water- repellent paint with added bituminous quartz powder, suitable for terraces and solar floors.

The product preserves and protects the support appearance for a long time, as it is designed for waterproofing surfaces from water filtering action.

Moreover IMPERMEABILIZZANTE PER TERRAZZE has good elasticity and adhesion to the support.

APPLICATION

- The surface to be treated must be dry.
- Make sure that the substrate is dry and free from grease, oil or dust traces.
- Proceed applying PRIMER CONSOLIDANTE insulation.
- Once the surface is dry apply with brush or roller, 1 or 2 coats of IMPERMEABILIZZANTE PER TERRAZZE ready to use or dilutable with water as necessary.

TECHNICAL DATA	
Nature of the bond	N/A
Viscosity	
Drying Time	2 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	4-5m ² /Lt
Specific weight	1,637Kg/Lt
Colors	Grey
Dry aspect	
Wet aspect	
Storing	Max Temp. +30°C, Min T. +5°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water
Packing	4LT,14LT
CHARACTERISICS	
Characteristics:	Quarzo.
Can be applied on:	Walls,Wood.
for:	Esterno.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Roller,Brush.
Related products:	PRIMER CONSOLIDANTE.

SAFETY INSTRUCTIONS

The product does not require any labelling under the Decree 285 of 16/7/98 and subsequent amendments and updates. Use the product in accordance with the relevant health and safety regulations of the country. Do not dispose of the containers in the environment after use; let the residues dry and treat them as special waste. For further information please refer to **SSR36** safety data sheet.

ITEM SPECIFICATION

Water- repellent paint with added bituminous quartz powder, suitable for solar floors. Applications to be made on already prepared surfaces of water- repellent paint for solar floors. IMPERMEABILIZZANTE PER TERRAZZE cod.IT01 based on bituminous quartz powder, at least into 2 layers, determined in quantities by the substrate absorption. Supply and installation of material € per sqm.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.