

PROTETTIVO PER GRANIGLIATO

Water-repellent, acrylic consolidating, solvent based product.

DESCRIPTION

PROTETTIVO PER GRANIGLIATO is a product based on solvent acrylic resins, designed and formulated for the protection of internal and external supports, particularly subject to the erosive action of water or atmospheric agents.

The product is water-repellent and washable, as it prevents water from penetrating the substrate.

PROTETTIVO PER GRANIGLIATO, in addition to protecting the substrate, it revives its colour, giving it a shiny appearance.

PROTETTIVO PER GRANIGLIATO finds application on various types of supports, such as plastic shot blasting, granimarble, cement, terracotta, carparo, Lecce stone, slabs, etc..

APPLICATION

Surfaces in plastic shot blasting, granimarble, cement, terracotta, carparo, Lecce stone, slabs:

Remove, by brushing or washing, the surface crusts and dirt on the surface.

In the case of mould, treat the surface with SCIK BONIFIK.

Make sure the support is well dry and proceed with a brush, roller or spray, applying 1 coat of PROTETTIVO PER GRANIGLIATO ready to use.

Advices

We recommend during the application of the product, to protect the floor and to make sure that the product evaporates completely before returning to the room.

Avoid the application of the product in the presence of humidity.

Apply the product when the substrate is completely dry.

TECHNICAL DATA	
Nature of the bond	Synthetic solvent acrylic resins in dispersion
Viscosity	
Drying Time	6 h at touch, 12-24 h complete.
Thinning	Ready to use
Yield	10-15m ² /Lt
Specific weight	0,800Kg/Lt
Colors	Trasparente satinato
Dry aspect	Satin, transparent
Wet aspect	
Storing	Max Temp. +30°C, Min T. +0°C
Stability	2 years (in sealed, unopened original packing)
VOC	µGr/m ³
TVOC	N/A
PH	N/A
Cleaning	Water ragia@diluyente sintetico
Packing	20LT,5LT
CHARACTERISTICS	
Characteristics:	Linea idrorepellenti.
Can be applied on:	Walls,Wood.
for:	Interiors ed Exteriors.
Certifications:	
TOOLS AND RELATED PRODUCTS	
Tools:	Roller,Brush,Sprayer.
Related products:	SCIK BONIFIK.

SAFETY INSTRUCTIONS

Flammable; keep out of reach of flames and sparks; do not smoke; harmful; avoid contact with skin and eyes; do not inhale gases, fumes, vapours, aerosols; if swallowed do not induce vomiting; seek medical advice immediately and show this container or label; keep out of the reach of children; toxic to the environment; do not empty into drains or into water. See SSR66 Safety Data Sheet for further information.

SPECIFICATION ITEM

Solvent-based acrylic solvent consolidating water-repellent protection for indoor and outdoor use.

NOTES

- Please note that due to technical reasons caused by the tinting of the product the indicated Specific Weight of the product may differ from the Package Net Weight.
- In the original, sealed containers and in appropriate temperature conditions . The period of stability is purely indicative, and refers to the minimum stability period of the product if stored ideal conditions according to the instructions provided. If properly stored the products stability period may extend several years.
- Rivedil ensures that the information herein is provided to the best of its experience and its technical and scientific knowledge , however , being elements such as weather conditions, labor , tools, quality of third party products and others, not under the direct control of the Rivedil , this document does not constitute a warranty , nor does Rivedil authorize its agents and / or representatives to provide any kind of warranty based on the information contained in this document . We recommend that you always check the suitability of the product to each specific instance . This supersedes all previous editions.



COLORIFICIO RIVEDIL di COSIMO CODARDO
 Via Prov.le per Veglie Km 0,500 - 73015 Salice Salentino (Le) Italy
 Tel. (+39) 0832 731293 - (+39) 0832 731273
 P.IVA 01122590753
 www.rivedil.com - export@rivedil.com